

SECOR INTERNATIONAL INCORPORATED

www.secor.com 3017 Kilgore Road, Suite 100 Rancho Cordova, CA 95670 916-861-0400 TEL 916-861-0430 FAX

October 19, 2005

Ms. Colleen Stone California Regional Water Quality Control Board North Coast Region 5550 Skylane Boulevard Suite A Santa Rosa, California 95403

RE: Quarterly Summary and Monitoring Report – Third Quarter 2005

SECOR Project No.: 77CP.60009.01.0220

Dear Ms. Stone:

On behalf of ConocoPhillips, SECOR International Incorporated (SECOR) is forwarding the quarterly summary report for the following location:

Service Station

Location

Former Bulk Plant No. 0220

720 North Franklin Street Fort Bragg, California

Sincerely,

SECOR International Incorporated

Thomas M. Potter Project Scientist

Som w J.

Attachments: SECOR's Quarterly Summary Report - Third Quarter 2005

cc: Mr. Thomas Kosel, ConocoPhillips

Mr. David Smith, North Coast Petroleum, Inc. 720 N Franklin St. Fort Bragg, CA

95437

QUARTERLY SUMMARY REPORT Third Quarter 2005

Former Bulk Plant No. 0220 720 North Franklin Street Fort Bragg, California

City/County ID #:

Fort Bragg

County:

Mendocino

SITE DESCRIPTION

The site is located near the north end of the City of Fort Bragg at the corner of Franklin and Spruce Streets. Pudding Creek is located approximately 1,200 feet north of the site, and the Pacific Ocean is located approximately 2,400 feet west of the site. The facility was built in 1924 and currently consists of a storehouse, an office, a drum storage and filling area, five above ground storage tanks (ASTs), a pump area, and loading racks. Former components of the facility included two 550-gallon underground spill contaminant tanks (SCTs) used to collect overflow spillage and overflow spillage with waste oil respectively, and a pump area. Product was historically supplied to the bulk plant by rail and for the past 30 years by truck. There are two separate unloading racks; one was to service rail cars (currently not in use) and the other to service trucks. Both the train and truck unloading racks serviced the bulk storage ASTs and loading rack via underground pipelines. The tank farm has a capacity of 85,000 gallons of storage with four 20,000-gallon ASTs and one 5,000-gallon AST.

PREVIOUS INVESTIGATIONS AND REMEDIAL ACTIVITIES

In September 1988 Kaprealian Engineering Incorporated (KEI) conducted a preliminary site investigation that included the installation of six borings for soil and groundwater sampling (EB-1 through EB-6). The borings were advanced to a total depth ranging from 17 to 19 feet bgs. Total petroleum hydrocarbons with gasoline distinction (TPHg) and total petroleum hydrocarbons with diesel distinction (TPHd) were detected in soil and groundwater at concentrations ranging from 80 milligrams per kilogram (mg/kg) to 340 mg/kg respectively.

On January 23, 1989, KEI oversaw the installation of four monitoring wells (MW-1 through MW-4) at the site. The wells were installed at depths ranging from 20 to 25.5 feet bgs. Groundwater was encountered at depths ranging from 10.5 to 14 feet bgs. All soil samples taken from the monitoring wells recorded non detectable concentrations of TPHg, TPHd, and benzene, toluene, ethyl-benzene and total xylenes (collectively BTEX) except the ten foot sample from MW-4 which recorded a concentration of 790 milligrams per kilogram (mg/kg) of TPHg. Groundwater samples taken from the wells contained concentrations of benzene ranging from 4.1 to 87 micrograms per liter (μ g/L), concentrations of TPHg ranging from 2800 to 8800 ug/L, and concentrations of TPHd ranging from 1900 to 160,000 μ g/L.

SECOR

On March 29, 1989, KEI oversaw the installation of five additional monitoring wells (MW-5 through MW-9) at the site. The wells were installed at depths ranging from 18 to 20 feet bgs. Groundwater was encountered at depths ranging from 9 to 15.5 feet bgs. Soil samples from the borings were analyzed for TPHg, TPHd, and BTEX. TPHg was found in the 10-foot sample from MW-5 at a concentration of 1.1 mg/kg. TPHd was detected in soil from MW-6 at a concentration of 400 mg/kg.

On July 26, 1989, KEI oversaw the installation of two additional monitoring wells (MW-10 and MW-11) at the site. The wells were installed at depths ranging from 19 to 20 feet bgs. Soil samples from the borings were analyzed for TPHg, TPHd, and BTEX. TPHg and TPHd were found in the 13-foot sample from MW-11 at concentrations of 31 mg/kg and 120 mg/kg respectively. Groundwater samples taken from the MW-10 and MW-11 contained TPHd at concentrations of 180 ug/L and 540 ug/L respectively.

On September 1, 1995, KEI oversaw the installation of one additional groundwater monitoring well (MW-12) at the site. The well was installed at a depth of 19 feet bgs. Soil samples from the borings were analyzed for TPHg, TPHd, and BTEX. All soils recorded non-detectable concentrations of all analytes. Groundwater samples taken from the well contained TPHg, TPHd, benzene, toluene, and ethylbenzene at concentrations of 430 ug/L, 220 ug/L, 7.2 ug/L, 51 ug/L, and 12 ug/L respectively.

In December 1996, KEI oversaw the removal of two 550 gallon spill containment tanks. During the excavation KEI conducted a limited excavation around the vicinity of the tanks. In February 1997, Pacific Environmental Group (PEG) conducted a Phase I site assessment of the site. To follow up with this assessment, on September 25, 1997, PEG oversaw the advancement of five soil borings (SB-1 through SB-4 and HB-1). The borings were advanced to depths ranging from 17.7 to 35 feet bgs. Soil samples analyzed from HB-1, SB-1, and SB-4 contained relatively low concentrations of TPHg and TPHd. The highest concentration of TPHg (37 mg/kg) and TPHd (28 mg/kg) were seen in the five-foot sample taken from SB-1.

In February 1998, the quarterly monitoring activities at the site were taken over by Gettler-Ryan (GRI).

In September 1998, SHN Consulting Engineers & Geologists Inc. (SHN) prepared an interim corrective action plan (ICAP) for the site. In the ICAP, SHN recommended the installation of a supplemental oxygen source to enhance bioremediation processes at the site.

On April 12, 1999, SHN performed an additional subsurface investigation at the site. During the investigation, ten soil borings (SB-101 through SB-110) were advanced and abandoned, aquifer slug tests were performed on existing groundwater monitoring wells, and petroleum hydrocarbon fingerprinting was performed on the groundwater from the site. Based on the results of these three tests, SHN recommended the installation of a biosparge system.

During May and June of 2000, SHN supervised the installation of one bioventing test well, two biosparge wells, and three bioventing observations wells. A bioventing pilot test and a biosparge pilot test were conducted to determine the effectiveness of each method for site

SECOR

remediation. Based on the results of the pilot tests, the anticipated radius of influence for a bioventing system is 30 feet per well.

On December 5, 2002, SHN recommended the installation of 7 additional bioventing wells and 20 additional ozone sparge points at the site.

On October 8 and 9, 2003, SHN oversaw the installation of biovent wells (BV-2 through BV-8).

On October 7 through 10, 2004, SHN oversaw the installation of 20 ozone sparge wells (SP-1 through SP-20). Soil samples were analyzed from all the borings. The highest concentrations of hydrocarbons were found in soils taken from SP-7 and SP-18.

THIRD QUARTER 2005 SUMMARY

Quarterly groundwater monitoring and sampling were conducted by TRC on August 4, 2005 in accordance with RWQCB-NCR MRP No. R1-2003-0107 (Attachment 1). The current groundwater monitoring network consists of six onsite wells (MW-1 through MW-4, MW-6 and MW-7) and six offsite wells (MW-5 and MW-8 through MW-12) located in Spruce Street and Franklin Street. Wells MW-1 through MW-3, MW-5, MW-10, MW-11 and MW-12 are sampled semi-annually (first and third quarters). Wells MW-6, MW-7, and MW-9 are sampled annually, and wells MW-4, MW-8, and MW-11 are sampled quarterly. All wells will be monitored for depth to groundwater quarterly. The monitoring and sampling plan is summarized in Table 2.

During the third quarter 2005, depth to groundwater was gauged in each monitoring well. In accordance with the Monitoring Reporting Program (MRP), groundwater samples from each monitoring well were monitored quarterly for dissolved oxygen, dissolved carbon dioxide, oxidation-reduction potential, pH, temperature and conductivity. The samples were also analyzed for TPHg TPHd, benzene, toluene, ehtylbenzene, and total xylenes (collectively BTEX), MtBE, the schedule is summarized in Table 2. Additionally, the headspace in each monitoring well was monitored quarterly for percent oxygen, percent carbon dioxide, and percent organic vapor.

Historical groundwater elevation and analytical data through the third quarter 2005, TRC's monitoring and sampling procedures, certified laboratory analytical report, chain-of-custody documentation, field data sheets, and waste water disposal procedures are presented in TRC's Quarterly Monitoring Report July Through September 2005, included in Attachment 2. A summary of the third quarter 2005 groundwater monitoring and sampling results is presented below.

THIRD QUARTER 2005 MONITORING AND SAMPLING RESULTS

Groundwater Monitoring and Gradient Data

Depth to groundwater in the twelve site wells ranged from approximately 11.25 feet (MW-9) to 15.45 feet bgs (MW-5). Groundwater levels reported during the third quarter 2005 were consistent with historical levels, which have ranged between 5.08 feet and 24.87 feet bgs.

Groundwater elevations in the site wells during the third quarter 2005 ranged from approximately 59.70 feet (MW-10) above mean sea level (msl) to 64.56 feet above msl (MW-6). Regional groundwater flow during the third quarter 2005 was northwesterly at a hydraulic gradient of 0.02 feet per foot, which is consistent with the groundwater flow direction and hydraulic gradient data reported over previous quarters (Table 3). A regional groundwater elevation contour map was prepared by TRC using monitoring data collected on August 4, 2005 and is presented in Attachment 2.

Groundwater Quality Data

Groundwater samples were collected from wells MW-1, MW-2, MW-3, MW-4, MW-5, MW-8, MW-10, MW-11, and MW-12 on August 4, 2005. Groundwater analytical results and TPHd, TPHg, benzene, and MtBE isoconcentration maps are included in TRC's *Quarterly Monitoring Report July Through September 2005* (Attachment 2).

The dissolved plume within the shallow zone continues to be centered around the former ASTs located on the north edge of the property. The heart of the plume is centered at MW-8 and MW-4. Concentrations of TPHg, TPHd, BTEX, and MtBE this quarter were generally consistent with historical levels.

The highest concentrations of petroleum hydrocarbons were detected in well MW-4 during the third quarter 2005. During the third quarter 2005, the groundwater sample collected from MW-4 had site maximum concentrations of TPPH (16,000 ug/L) and TPHd (640,000 ug/L). The concentrations of TPPH and TPHd were generally consistent with historical values. MtBE and BTEX were not detected in any wells sampled during this period except MW-10 with MtBE at 4.1 µg/L. These results are consistent with recent stable trends.

Plume Status

In the most recent samples collected from each well, petroleum hydrocarbons in shallow groundwater were detected at MW-1, MW-3, MW-4, MW-8, MW-10, and MW-11. The extent of dissolved petroleum hydrocarbons in shallow groundwater is defined downgradient (northwest), except for TPHd at MW-10, and cross-gradient (southwest-northeast) of the site, except for low concentrations of TPPH and TPHd at MW-6. The extent of dissolved petroleum hydrocarbons in shallow groundwater has been defined upgradient of well MW-4 by no detected concentrations of petroleum hydrocarbons in MW-5.

MtBE has been detected in both on-site and off-site wells. Generally, detection is sporadic, at low concentrations, and limited to on-site wells MW-1 and MW-2 and offsite wells MW-8 through MW-12. Most recently, the highest recorded concentration of MtBE in these wells was 43 µg/L reported in November 2004 at MW-10. Since that time, MtBE concentrations in all wells has declined.

BTEX have also been detected in both on-site and off-site wells. Generally, detection is sporadic and concentrations are low. BTEX were not detected in the most recent sample collected from each well.

STATUS OF REMEDIAL ACTION

On August 9, 2005, SHN installed new ball valves and pressure gauges to repair the ozone separation system. After the installation was complete the system was then turned on. Shortly after power was applied, a short on the ozone generator circuit board occurred and the system went down. A visual inspection identified the circuits went bad and therefore the system is non operational at this time.

WASTE DISPOSAL

The volume of purged groundwater generated and disposed during the quarterly groundwater monitoring event is documented in TRC's Quarterly *Monitoring Report, July Through September 2005* dated September 15, 2005 (Attachment 2).

RECENT SUBMITTALS/CORRESPONDENCE

Submitted the Quarterly Summary Report - Second Quarter 2005.

Received letter from CRWQCB-NCR dated August 26, 2005 for revised MRP

Monitoring Report April through June 2005 dated June 6, 2005.

SECOR submitted the Addendum to Quarterly Summary Report – Second Quarter 2005 on September 23, 2005.

WORK COMPLETED IN THIRD QUARTER 2005

- 1. TRC performed quarterly groundwater monitoring and sampling at the site.
- 2. SHN performed operations and maintenance including installation of ball valves and pressure gauges to the ozone system.
- 3. SECOR prepared and submitted 2nd quarter quarterly summary and monitoring report.

PROPOSED ACTIVITIES FOR FOURTH QUARTER 2005

- 1. TRC to conduct groundwater monitoring and sampling.
- 2. SECOR to prepare and submit quarterly summary report.
- 3. SHN to perform operations and maintenance.
- 4. SECOR to evaluate options of repair or replacement of ozone system.

LIMITATIONS

This report presents our understanding of existing conditions at the subject site. The conclusions contained herein are based on the analytical results, and professional judgment in accordance with current standards of professional practice; no other warranty is expressed or implied. SECOR assumes no responsibility for exploratory borings or data reported by other consultants or contractors.

Sincerely,

SECOR International Incorporated

Adrian Perez, P.E. Associate Engineer

Attachments: Table 1 Soil Boring and Well Construction Details

Table 2 Monitoring and Sampling Plan

Table 3 Historical Groundwater Flow Direction and Gradient Data

Table 4 Sample Parameters

Attachment 1 RWQCB-NCR MRP No. R1-2003-0107

Attachment 2 TRC's Quarterly Monitoring Report July Through

September 2005, Dated August 4, 2005

TABLES

Table 1 Soil Boring and Well Construction Details

Former Tosco Bulk Plant No. 0220 720 North Franklin Street Fort Bragg, California

															Į			
		10C/	Ground								Fliter	Filter	Filter	Filter	Вел-	Веп	Веп	Веп-
		PVC	Surface		Well			Well Screen	creen		Pack	Pack	Pack	Pack	tonite	tonite	tonite	tonite
Well	Date	Elevation	Elevation	De	Depth	Diameter	T	Top	Bot	Bottom	Тор	Top	Bottom	Bottom	Тор	Тор	Bottom	Bottom
Ġ.	Installed	(feet, MSL)	(feet, MSL)	(feet, bgs)	(feet, MSL)	(inches)	(feet, bgs)	(feet, MSL)										
MW-1	01/23/89	-	_	20.5	1	2	10.5		20.5	-	8	1	20.5	1	9	1	8	-
MW-2	01/24/89	:	-	25.5	ı	2	10.5	;	25.5	ı	8	1	25.5	1	9	-	8	:
MW-3	01/24/89	-	-	22.0	1	2	10.0	-	22	ı	8	1	22	1	9	1	8	1
MW4	01/24/89	. 1	-	50	-	2	10.0		20	ı	8	1	20	. 1	9	_	8	:
MW-5	03/29/89	:	ı	20	-	2	10.0	ı	20	ı	8	ı	20	1	9	ı	8	ı
MW-6	03/29/89	ı	1	18.0	1	2	8.0	-	18	_	8	-	18	1	9	1	8	:
MW-7	03/29/89	-	1	18.0	-	2	8.0	1	18	1	8	ı	18	-	9	-	8	-
MW-8	03/29/89		_	18.0	ı	2	8.0	-	18.0	1	9	ı	18	1	4	1	9	1
MW-9	03/29/89	:	ı	19.0	1	2	9.0	ı	19.0	1	7	1	19	1	5	_	7	ı
MW-10	7/26/89		1	19	_	2	4.0	:	19.0	1	3	ı	19	:	1	1	3	1
MW-11	7/26/89		-	07	_	2	4.0	ı	20.0	ı	3	_	20	_	1	1	3	-
MW-12	9/1/95	_		20.0	ı	2	4.0	ı	19.0	;	3	1	19	_	2	1	3	-
Exnianations:	.suc																	

xplanations:

feet, MSL = Elevation in feet relative to mean sea level.

TOC = Top of well casing.

bgs = Below ground surface.

PVC = Polyvinyl chloride.

– Data unavailable

Table 2
Monitoring and Sampling Plan
ConocoPhillips Bulk Plant No. 0220
720 North Franklin Street
Fort Bragg, California

	First Quarter	arter	Second & Four	Fourth Quarters	Third Quarter	ıarter	Work Completed	pleted	Work Completed	pleted
WellID	MRP No. R1-2003-0107	2003-0107	MRP No. R1-2	. R1-2003-0107	MRP No. R1-2003-0107	2003-0107	During Second Quarter	d Quarter	During Third Quarter	Quarter
	Monitor DTW	Sample	Monitor DTW	Sample	Monitor DTW	Sample	Monitor DTW	Sample	Monitor DTW	Sample
MW-1	+	-	-		-	1	·		1	-
MW-2	-	τ-	τ -		-	-	-		ζ-	_
MW-3	<u>-</u>	<u></u>	-		_	-	_		- -	-
MW-4	τ-	-	_	_	_	_	_	_	-	_
MW-5	-		_		_	_	_		_	_
MW-6	-	-	_		-		_		-	
MW-7	_	_	_		ζ-		_		-	
MW-8	_	-	_	_	•	_	-	-	_	-
6-MM	-	_	_		-		Υ-		-	
MW-10	_	-	_		_	-			-	-
MW-11	_	-	ζ-	-	_	-	-	_	-	_
MW-12	-	-	-		-	- -	-			-
Totals	12	12	12	ო	12	တ	12	က	12	o

Table 3 Historical Groundwater Flow Direction and Gradient Data

ConocoPhillips Bulk Plant No. 0220 720 North Franklin Street Fort Bragg, California

Date	Average Groundwater Flow Direction	Average Gradient (ft/ft)
2/19/1999	NW	0.02
5/19/1999	NW	0.02
8/5/1999	WNW	0.03
11/24/1999	NW	0.04
2/15/2000	NW	0.02
3/11/2000	NW	0.02
8/9/2000	WNW	0.01 to 0.06
11/27/2000	WNW	0.01 to 0.04
2/14/2001	NW	0.02 to 0.07
5/11/2001	NW	0.01 to 0.03
8/9/2001	NW	0.01 to 0.05
11/30/2001	NW	0.02 to 0.04
2/7/2002	NW	0.01 to 0.03
5/10/2002	NW	0.01 to 0.04
8/15/2002	NW	0.02 to 0.04
11/14/2002	NW	0.02 to 0.06
2/13/2003	WNW	0.01 to 0.03
5/16/2003	NW	0.01 to 0.02
8/12/2003	NNW	0.01 to 0.07
12/22/2003	NW	0.02
2/24/2004	NW	0.02
5/6/2004	NW	0.02
8/4/2004	NW	0.02
11/10/2004	NW	0.02
2/3/2005	NW	0.02
5/5/2005	NW	0.02
8/4/2005	NW	0.02

Notes:

ft/ft Feet per foot
NW Northwest
WNW West Northwest
NNW North Northwest

Historical groundwater flow directions above are interpreted by SECOR based on a review of historical figures created by Gettler-Ryan Inc. and TRC.

Table 4 Sample Parameters

ConocoPhillips Bulk Plant No. 0220 720 North Franklin Street Fort Bragg, California

2 27	NEW SE	经证据是	医位置数数		公式發展	对于" "		Sept.	和主义的。	lead Space	工學院並列於
		Pre-Purge	Post Purge	Dissolved	Oxidation	J. C. C.	Temper				
	10	Dissolved. Oxygen	Dissolved : Oxygen	Carbon	Reduction Potential	Conductivity	ature 1				13000000000000000000000000000000000000
Date Sam	bian 1823	は、人などのようには	ACTOR NO.	Sharakara is	(Coming)	(µS/cm)	2(°C)	S.P.H.S.	Carbon Dioxide;	Oxygen,	Organic Vapor
MW-1	08/22/95										
	05/19/99	 0.18	0.21	_					-		
	08/05/99	3.70	2.35			-			-		
	02/15/00	3.85	3.76		34						
	08/09/00	4.09	4.48	5.5	180						
	05/05/04	4.63	- 4.40	-	155						
	08/04/04	4.63		- <u>-</u>	14						
	02/03/05	2.20		15	30	338	21.3	5.89	0.60	21.60	0.00
	05/05/05	2.08		8	121	270	14.9	5.89	0.10	20.90	0.00
	08/04/05	1.82	**	18	190	156	14.9	5.83	0.10	20.90	0.00
		,,,,,,,				. 100	17.0	0.00	0.10	20.50	0.00
MW-2											··
	08/22/95			_		_	_		_		
	05/19/99	0.28	0.32		_	_		_		_	
	08/05/99	6.37	6.86	2	66.1	_			_		_
	02/15/00	7.87	8.05	_	213		_			_	_
	08/09/00	6.58	6.52	ND	254			-			_
	02/24/04	7.49		35	174		_	_			
	05/06/04	6.32		_	163			-			
	08/04/04	4.26	_	-	10	_			-		_
	02/03/05	5.77	-	3	124	173.6	23.1	6.05	1.00	20.70	0.00
_	05/05/05	5.54		3	093				0.60	20.20	0.00
	08/04/05	5.46		6	208	151	15.0	6.15	0.00	20.90	0.00
MW-3											
	08/22/95	-			_						1
	05/19/99	0.28	0.38	-							
	08/05/99	5.30	5.11		-			-		_	
	02/15/00	6.50	6.40		213				_		
	08/09/00	4.88	5.05	ND	248	-		-		-	
	02/24/04	3.19		50	173	-					
	05/06/04	3.75			165					-	
	08/04/04	4.21			10						-
	11/10/04	3.20			- 40	404.0				-	-
	02/03/05 05/05/05	3.87 4.02	-	6 4	48 85	191.9	22.5	6.04	0.30	21.60	0.00
	08/04/05	3.20		10	212	173	 15.0	7.46	0.20 0.20	20.90	0.00
	20124100	V.2V	 -	- '0	12	1/3	10.0	7.40	0.20	20.90	0.00
MW-4		<u>-</u>			· · · · · · · · · · · · · · · · · · ·		 			 	
	08/22/95									_	
<u> </u>	05/19/99	0.18	0.17	1.7	68.5	_			_	 -	
	08/05/99	1.22	1.30	4.2	48.2		_	-		_	
	11/24/99	3.81	4.55	16	474	_					
	02/15/00		5.76	-	56					_	
	05/11/00	4.90	4.01	5.2	94	_					-
	08/09/00	3.22	3.09	8.9	34			_			_
	11/27/00	2.75	2.70	ND	46	_					=
	02/14/01	6.8	3.2	22	63	<u> </u>					
	05/11/01	5.2	3.4	7.5	44	_					
	08/09/01	6.4	3.3	12	54	_					

evisit organ	しゅんごう きかんしきんご	เขาสะสองกระทธิย์(1.2)	Kiralistala ritariation	us in Cottagoral Assert	CHECKS WITH NEW	Main and was some the car	See Allen 1881	Separations.	III. COMPANIAN AND AND AND AND AND AND AND AND AND A		
		Pre-Purge	Boot Brees	Dissolved	學等是非常	13 101	企业2019		, in	ead Space	
35 (C) (41) ju		Dissolved	Post Purge	33 Z RAS 15 1 2 2	Oxidation	经验的证据	Temper				
10.0	电影型的电话	Oxygen	Dissolved Oxygen	Carbon." Dioxide	Reduction Potential	Conductivity	ature	軍黨	AND THE SAME OF	Haw Mark	电影大学 的复数
Date Sal	mpled	a magazi	777 737 537	The state of the s	Short-Lang Bry Balebreef etc.	(µS/cm)	* (°C)	«pH-	Carbon Dloxide	Oxygen	Organic Vapor
	11/30/01	5.7	3.4	21	55	-	-			_	-
	02/07/02	2.5	3.3	11	63				-		_
	05/10/02	1.1		18	61		-				
	08/15/02	2.6		20	-15						<u></u> _
	11/14/02	1.6		27	106	-					
	02/13/03	1,4		11	18		-		-		_
	05/16/03	1.4	-	13	55			-		-	
	08/12/03	1.3		39	30			_		_	_
	05/06/04	4.51			10				_	-	
	08/04/04	4.64			9						
	11/10/04	1.48	_ ~				-				-
	02/03/05	1.21		11	16	295	20.1	6.02	0.10	21.60	0.00
	05/05/05	0.84		15	147	218	14.5	6.07	0.00	20.90	0.00
	08/04/05	1.53	-	27	189	162	14.4	6.08	0.10	20.90	0.00
MW-5											
	08/22/95		_			-	_	-			
	05/19/99	0.32	0.38	-		-					
	08/05/99	6.94	4.31		-	-					
	02/15/00	9.11	8.96	-	129	-	-				
	08/09/00	6.45	4.90	5.70	94		ı				
	05/06/04	3.29			166	-	ı				
	08/04/05	2.77		21	37	167.8	15.0	5.76	0.10	20.90	0.00
MW-6				1						L .	
	08/22/95	-		<u> </u>			-			-	1
	05/19/99	0.32	0.32			-	-		-		
	08/05/99	5.11	5.10	_			-		_	_	
	02/15/00	6.23	5.90		203	-		_		-	
	08/09/00	7.06	6.84	ND	266			-	_		-
	02/24/04	2.19		60.00	170	-	_	-		-	
	05/06/04	1.59		-	210	-					-
	02/03/05	1.71		13	21	203.5	22.7	6.09	0.40	21.70	0.00
	05/05/05	1.65		6	98	-			0.50	20.90	0.00
	08/04/05	4.44	-	7	203	165	16.0	6.02	0.10	20.90	0.00
MW-7					ļ						
	08/22/95		_			-					_
	05/19/99	0.38	0.51	1.6	50.1				_		
	02/15/00		8.56		228	_	-		_	_	
	02/14/01	6.4	7.3	12	294	-				-	
	02/07/02	6.5	6.8	ND<10	233	-			"		
	02/13/03	5.6		ND<10	85		-	-	_	-	
	02/24/04	5.57		35	223		_	_	-	-	
	05/06/04	5.34			209		-	-			
	02/03/05	6.57		3.00	98	183.7	21.7	5.93	0.30	21.60	0.00
	05/05/05	4.60		5	088		-		0.00	20.90	0.00
	08/04/05	3.17	-	8	161	161	15.0	5.89	0.10	20.90	0.00
				<u> </u>	ļ						
MW-8					ļ						
	08/22/95								-		_
	05/19/99		0.10	2.1	13.1					-	
	08/05/99		2.00	3.6	48.8						
	11/24/99	4.87	5.21	17	523						-
	02/15/00	4.94	3.52	-	6						
	05/11/00	5.56	2.92	6.2	77						
	08/09/00	2.45	2.44	7.5	52		_	l –	-		-
	11/27/00	1.95	2.16	5.3	64						

.a.d-∴4./	rate and the second	DEFES PEDISAN	SPECIAL ASSESSED.	net a literatura entra	NAME OF THE PERSON	The substitutions	ತ ್ರಾಣಕ್ಕೆ ಪ್ರಕ್ರಿಯ	320 Zida	NATIONAL PROPERTY OF THE	lasticass.	water the control of
		Pre-Purge	Post Purge	Dissolved	Oxidation-		Temper			au Spaci	
多数是 (3 (1.00)	Dissolved	Dissolved	Carbon	Reduction	Conductivity	ature	4			
Date San	noled	Oxygen	Oxygen	, Dioxide		ું (μS/cm)		4	Carbon Dloxide	Overson	A Organic Wange
	02/14/01	4.1	3.2	20	62	The second secon			Wadinatirpioxide%	JOY Marit	(#Gi BarilovijaBotz
	05/11/01	4.1	3.4	9.5	61	-					
	08/09/01	5.5	4.8	10	55	-		-		-	
	11/30/01	5.4	5.0	16	49			-			
	02/07/02	2,5	3.0	13	57						
	05/10/02	1,3		12	81			-			
	08/15/02	2.6		12	2					_	
· · · · ·	11/14/02	1.6		20	170		_	-			-
	02/13/03	1.5		11	-15	_		_			
	05/16/03	1.0		ND<10	60		_		_	_	
	08/12/03	1.4		35	50	_		_			
	02/24/04	1,24		95	1					_	
	05/06/04	5.02			-55	-	_	_			
	08/04/04	4.68		_	-83	_				_	
	11/10/04	2.08	_				_				
	02/03/05	2.28		76	96	665	14.6	5.49	0.30	21.60	2.30
	05/05/05	0.79		34	-101	372	15.5	6.24	0.00	20.90	0.00
	08/04/05	2.54	_	23	-30	354	15.8	6.47	0.00	20.90	50.10
				-			-				
MW-9											
	08/22/95	<u> </u>	-			_	-				
	05/19/99	0.82	0.84		43.9		-	_		-	_
	08/05/99	10.01	2.15	-			-	-	-	-	
	02/15/00	8.01	6.36		209	-	_	_			_
	08/09/00	6.11	4.69	6.2	221		-	1	-		
	02/24/04	4.14		50	164	-	-	-		-	
	05/06/04	3.92	_	-	146	-				_	
	02/03/05	5.21		9	32	190.6	17.9	5.86	2.00	21,10	0.00
	05/05/05	4.13		9	-50		_	_	1.10	18.60	0.00
	08/04/05	6.42		25	127	191	16.7	6.29	0.02	20.90	0.20
MW-10	00100105								<u>-</u> .		
	08/22/95		-					-	<u> </u>		
	05/19/99	0.63	0.65	2.2	19.1			-			
	08/05/99 02/15/00	3.06 6.28	1.45 8.14	3.6	55.2 225	-					
	08/09/00	2.82	3.53	6.4	106	_	_				-
	02/14/01	3.7	4.7	15	168			_			
	08/09/01	3.4	4.4	12	154			-			-
l	02/07/02	4.5	5.6	13	170					-	
 	08/15/02	2.5	 	13	-15		-				
	02/13/03	4.6	_	ND<10	81						
	08/12/03	2.1		35	151		_	_			
	02/24/04	5.93	_	45	181	_				_	
	05/06/04	5.13		-	179				_		_
	08/04/04	0.00531	_	-	-40		_	_			_
	11/10/04	2.32				_			_		-
	02/03/05	4.1		16	75	297	16.2	5.84	0.60	21.90	0.00
	05/05/05	5.23		6	45	_		-	0.10	20.90	0.00
	08/04/05	1.53		20	41	283	17.8	5.90	0.20	20.90	0.00
MW-11											
	08/22/95	-					1	_	-		-
	05/19/99	0.22	0.20	1.9	66.7		-	-			_
	08/05/99	1.16	2.08	3.3	46.3		-			-	_
	11/24/99	5.71	6.33	11	533						
	02/15/00	6.08	6.66		185					-	-
	05/11/00	6.93	5.77	ND	173	_					_

Date Sampled	Pre-Purge Dissolved Oxygen	Post Purge Dissolved Oxygen	Dissolved Carbon Dioxide	Oxidation- Reduction Potential	Conductivity (µS/cm)	Temper ature		Carbon Dioxida		
		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Str C. Com. Dog.	1964 Bernar Green St.	A CONTRACTOR OF THE CONTRACTOR			* Caunoui Dioxida	Yoxygen	Porflauic zabor
08/09/00	2.64	3.56	6.4	58	-		-			
11/27/00	3.14	3.51	6.7	89		-	-			
02/14/01	5.9	6.9	9.3	264				-	-	
05/11/01	5.5	6.7	9.0	258						-
08/09/01	3.9	5.3	11	268				-		
11/30/01	5.1	6.4	13	189	-					-
02/07/02	3.9	4.8	13	266		-	-	-		
05/10/02	1.7	-	14	30		-			-	-
08/15/02	2.8		13	-31		-		-	<u> </u>	
11/14/02	1.1		22	126	-					
02/13/03	2.4	-	ND<10	61	-					
05/16/03	3.8		ND<10	220				-		
08/12/03	1.9		36	56		-	 -	-		_
02/24/04	2.81		50	202	-	-		-		
05/06/04	6.67			46	-	-				-
08/04/04	5.76		-	-31						-
11/10/04	1.64		_		-	1	-			_
02/03/05	7.13	_	5	38	308	18.1	5.86	0.10	22.10	0.00
05/05/05	5.60	<u></u>	6	-002	244	15.9	6.40	0.00	20.90	0.00
08/04/05	1.50	-	17	10	247	16.4	6.07	0.10	20.90	0.00
MW-12							├		 	
05/19/99	0.35	0.28		11.3						••
08/05/99	6.80	5.41	1.0	24.8	-	_		_	_	_
02/15/00	8.20	8.57		239				••		
08/09/00	7.19	6.58	ND	152						_
02/14/01	8.8	7.4	5.4	285	_	_	_			
08/09/01	6.8	6.1	5.0	266			-			
02/07/02	9	8.9	ND<10	244	_	-	-	-	-	
08/15/02	1.9		15	52				-		-
08/12/03	1.20		26	283		-	-	-	-	_
02/24/04	6.13		30	187		-		**		••
05/06/04	5,27		_	210		-				
08/04/04	5.28	_		-61	-	_	_			
02/03/05	8.37		6.00	69	270	16.2	6.27	0.60	0.00	21.80
5/5/2005	6.93		5	018		-	-	0.20	20.90	0.00
08/04/05	5.64		12	102	226	17.0	6.21	0.40	20.90	28.50

ATTACHMENT 1 RWQCB-NCR MRP NO. R1-2003-0107

Third Quarter 2005 Quarterly Summary and Monitoring Report
Bulk Plant No. 0220
720 North Franklin Street
Fort Bragg, California

SECOR Project No.: 77CP.60009.01.0220

California Regional Water Quality Control Board North Coast Region

Revised Monitoring and Reporting Program No. R1-2003-0107

fоr

Unocal Bulk Plant #0220 720 North Franklin Street Fort Bragg, California

Mendocino County

MONITORING

- 1. The depth to groundwater in all monitoring wells shall be determined to at least 0.01 foot increments quarterly. The results shall be reported in tabular form indicating the surveyed elevation of each well reference point, depth to groundwater from the reference point, and the actual groundwater elevation. The data generated from the elevation readings must be referenced to mean sea level.
- 2. Groundwater in each monitoring well shall be monitored quarterly for dissolved oxygen, dissolved carbon dioxide, oxidation-reduction potential, pH, temperature, and conductivity.
- Headspace in each monitoring well shall be monitored quarterly using field instruments to measure percent oxygen, percent carbon dioxide, and organic vapor.
- 4. Groundwater in each monitoring well shall be sampled according to Table 1 (Attached). The analyses shall be performed by a state certified laboratory for total petroleum hydrocarbons as gasoline (TPH-g), total petroleum hydrocarbons as diesel (TPH-d), benzene, toluene, ethylbenezene, xylene (collectively identified as BTEX), methyl tertiary butyl ether (MTBE), dissolved methane, dissolved iron, dissolved manganese, nitrate, and sulfate (collectively identified as ADDITIONAL).

REPORTING

- 1. The following maps shall be submitted with each quarterly monitoring report:
 - A map of the facility showing the quarterly groundwater flow pattern, including the direction of the groundwater gradient and the location of all monitoring wells, and
 - b. A map of the facility showing the quarterly chemical concentrations.
- 2. The results of each quarter's elevation shall be reported in a tabular form indicating the surveyed elevations of each reference point, depth to groundwater from the reference point, and the actual groundwater elevation.

Monitoring & Reporting Program 2 No. R1-2003-0107

May 3, 2005

- 3. Sampling analytical and monitoring data from each quarter shall be summarized in tabular form, including all previously generated sampling data.
- 4. Monitoring reports shall be submitted to the Regional Water Board at a quarterly frequency. Monitoring reports shall be prepared by or under the supervision of a California Registered Engineer or Geologist. Monitoring reports shall be submitted to this office in accordance with the following schedule:

Reporting Period	<u>Due Date</u>
January, February, March (1 st Quarter)	April 15
April, May, June (2 nd Quarter)	July 15
July, August, September (3 rd Quarter)	October 15
October, November, December (4 th Quarter)	January 15

- 5. All monitoring reports, data, and depth to groundwater shall also be submitted electronically to the State Water Resources Control Board's Geographic Environmental Information Management System database (GeoTracker) as required by Title 23, Division 3, Chapter 16, Article 12 of the California Code of Regulations (i.e., AB2886 electronic reporting requirements)
- 6. An annual report shall be submitted to the Regional Water Board by January 15 of each year. The annual report serves as a document to evaluate data generated throughout each calendar year. This report needs to include a full evaluation of all data generated throughout the year, including concentration trend evaluation for all analyses performed, evaluation of all indicator parameters in terms of remedial effectiveness, conditions of the remedial system, and an overall evaluation of the effectiveness of the active remedial system.
- 7. The annual report shall also include all maintenance and operations records for the entire year. Records should include date of inspections, parameters measured, summary of visual observations made, and changes made to the operating system.

Ordered by

Catherine Kuhlman Executive Officer

May 3, 2005

050305_CHS_U8P_M&RP_revised

Information on AB2886 electronic reporting can be obtained on the Internet by following the Electronic Submittal of Information link on the GeoTracker home page at http://geotracker.waterboards.ca.gov/.

MRP Requirements

MRP No. R1-2003-0107 Sample requirments

ConocoPhillips Bulk Plant No. 0220 Fort Bragg, California

		TOR Dragg, Call		
Well ID	First Quarter	Second Quarter	Third Quarter	Fourth Quarter
MW-1	TPHg, TPHd, BTEX, MtBE		TPHg, TPHd, BTEX, MtBE	
MW-2	TPHg, TPHd, BTEX, MtBE		TPHg, TPHd, BTEX, MtBE	
MVV-3	TPHg, TPHd, BTEX, MtBE		TPHg, TPHd, BTEX, MtBE	
MVV-4	TPHg, TPHd, BTEX, MtBE, Additional	TPHg, TPHd, BTEX, MtBE	TPHg, TPHd, BTEX, MtBE, Additional	TPHg, TPHd, BTEX, MtBE
MW-5	TPHg, TPHd, BTEX, MtBE		TPHg, TPHd, BTEX, MtBE	
MW-6	TPHg, TPHd, BTEX, MtBE			
MVV-7	TPHg, TPHd, BTEX, MtBE			
MW-8	TPHg, TPHd, BTEX, MtBE	TPHg, TPHd	TPHg, TPHd, BTEX, MtBE	TPHg, TPHd
MW-9	TPHg, TPHd, BTEX, MtBE			
MW-10	TPHg, TPHd, BTEX, MtBE, Additional		TPHg, TPHd, BTEX, MtBE, Additional	
MW-11	TPHg, TPHd, BTEX, MtBE, Additional	TPHg, TPHd	TPHg, TPHd, BTEX, MtBE, Additional	TPHg, TPHd
MW-12	TPHg, TPHd, BTEX, MtBE, Additional		TPHg, TPHd, BTEX, MtBE, Additional	

Notes:

Additional = dissolved methane, dissolved iron, dissolved manganese, nitrate, sulfate

ATTACHMENT 2 TRC'S QUARTERLY MONITORING REPORT JULY THROUGH SEPTEMBER 2005

Third Quarter 2005 Quarterly Summary and Monitoring Report
Bulk Plant No. 0220
720 North Franklin Street
Fort Bragg, California

SECOR Project No.: 77CP.60009.01.0220

SEE TRC

3Q05 QMR